

MSDS *Material Safety Data Sheet*

Leather Pro

Nubuck Leather Protector

MSDS Number: TC439

Revision Date: January 25, 2010

Page 1 of 4

1 PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

Kärcher North America, Inc.
Prochem
325 S. Price Road
Chandler, AZ 85224

Contact: Prochem
Telephone Number: 480-899-7000
FAX Number: 480-786-9538
E-Mail: info@prochem.com
Web: www.prochem.com

Product Name: Nubuck Leather Protector
Revision Date: January 25, 2010
Version: New
MSDS Number: TC439

Emergency Telephone 800-535-5053 (INFOTRAC)

2 HAZARDS IDENTIFICATION

Route of Entry: Eyes; Skin; Inhalation;
Target Organs: Eyes; Skin;
Inhalation: Minimal respiratory tract irritation may occur with exposure to a large amount of material.
Skin Contact: May Cause Irritation.
Eye Contact: May Cause Irritation.
Ingestion: Ingestion is not applicable route of entry for intended use.

HMIS Rating H1/F0/PH0®

3 COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas #	Perc.	Chemical Name
34590948	2-6%	Dipropylene glycol methyl ether

OSHA Regulatory Status:

This MSDS contains valuable information critical to the safe handling and proper use of this product. This MSDS should be retained and available for employees and other users of this product.

MSDS *Material Safety Data Sheet*

Leather Pro

Nubuck Leather Protector

MSDS Number: TC439

Revision Date: January 25, 2010

Page 2 of 4

4 FIRST AID MEASURES

Inhalation: If symptoms develop, move victim to fresh air; if symptoms persist, obtain medical attention.
Skin Contact: Wash with soap and water. If irritation persists consult medical personnel.
Eye Contact: Immediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids occasionally to facilitate irrigation. Get immediate medical attention.
Ingestion: If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel. If injured party is conscious, give two glasses of water. Seek medical attention.

5 FIRE FIGHTING MEASURES

Flash Point: >212°F
Flash Point Method: Closed Cup

Wear self-contained breathing apparatus and other protective clothing. Use any standard agent - choose the one most appropriate for type of surrounding fire.

6 ACCIDENTAL RELEASE MEASURES

Keep away from drains and ground water. Keep all unnecessary personnel away. Spill area may be slippery. Pick up excess with inert absorbent material and place into separate waste container. Ventilate area and wash spill site after material pickup is complete. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

7 HANDLING AND STORAGE

Handling Precautions: Avoid contact with eyes, skin, or clothing; Consider normal working hygiene. Handle with care and avoid spillage on the floor (slippage). Keep away from sources of ignition; wash thoroughly after handling.
Storage Requirements: Store out of reach of children; keep container closed; store in a cool well-ventilated place away from strong oxidizing or alkaline product.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Normal room ventilation is satisfactory for limited use.
Protective Equipment: Safety Glasses/Gloves
Exposure Guidelines/Other: Dipropylene glycol methyl ether 34590-94-8 OSHA PEL 100 ppm/ 600 mg/m3

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Off-white opaque	Boiling Point:	N/D
Physical State:	Liquid	Freezing/Melting Pt.:	N/D
Odor:	Mild acrylic	Solubility:	Soluble
pH:	4.0 - 4.5	Spec Grav./Density:	8.40 lb/gal
Vapor Pressure:	N/D		
Vapor Density:	N/D		

VOC: 3.2%

MSDS *Material Safety Data Sheet*

Leather Pro

Nubuck Leather Protector

MSDS Number: TC439

Revision Date: January 25, 2010

Page 3 of 4

10 STABILITY AND REACTIVITY

Stability:	Product is stable under normal conditions.
Conditions to avoid:	None Known
Materials to avoid (incompatibility):	None Known
Hazardous Decomposition products:	Exposure to fire may liberate carbon dioxide, carbon monoxide, organic acids, and other unidentified thermal decomposition products from this product or its packaging.
Hazardous Polymerization:	Will not occur.

11 TOXICOLOGICAL INFORMATION

Toxicity Data:

Dipropylene glycol methyl ether 34590-94-8

Oral (LD 50): 5400 uL/kg - Rat

Inhalation (LC 50): Not listed on RTECS

Skin irritation: Mild - Rabbit

Eye irritation: Mild - Rabbit

Sensitization: Not considered an occupational sensitizer

12 ECOLOGICAL INFORMATION

Refer to Section 6 for information regarding accidental releases and Section 15 for regulatory reporting information.

13 DISPOSAL CONSIDERATIONS

Dispose of in accordance with local regulations.

14 TRANSPORT INFORMATION

Ship in accordance with 49 CFR parts 100-185. Non-hazardous for air, sea and road freight.

MSDS *Material Safety Data Sheet*

Leather Pro

Nubuck Leather Protector

MSDS Number: TC439

Revision Date: January 25, 2010

Page 4 of 4

15 REGULATORY INFORMATION

COMPONENT / (CAS/PERC) / CODES

*Dipropylene glycol methyl ether (34590948 2-6%) MASS, OSHAWAC, PA, TSCA, TXAIR, WHMIS

REGULATORY KEY DESCRIPTIONS

All components are listed on TSCA

MASS = MA Massachusetts Hazardous Substances List

OSHA = OSHA workplace Air Contaminants

PA = PA Right-To-Know List of Hazardous Substances

TXAIR = TX Air Contaminants with Health Effects Screening Level

WHMIS = workforce Hazardous Material Information System

16 OTHER INFORMATION

This document is prepared in accordance with 29 CFR 1910.1200. The purpose of this section is to ensure that the hazards of all chemicals produced or imported are evaluated, and that information concerning their hazards is transmitted to employers and employees.

All information appearing herein is based upon data obtained from the raw material manufacturer and/or recognized technical sources. While the information above is believed to be true and accurate, the author makes no representations as to its accuracy or sufficiency. Conditions of use are beyond the manufacturer's control; therefore the users are responsible to verify this data under their own particular conditions, applications and regulations to determine if the product is suitable for their particular purposes. The users assume all risks of product use, handling, disposal, reliance upon, publication or use of the information contained herein. This information applies only to the product designated above and does not necessarily apply to its use in combination with other materials, products, chemical compounds, structures or processes.

Prepared by: EHS Manager

Phone Number: [480] 899-7000

END OF MSDS DOCUMENT